


ネジ穴付Uークランプ

U-CLAMP with THREAD HOLE



- 材 質 S45C
 - 硬 度 HRC30~35°
 - 仕 上 黒染
- (1ヶ単位)



(寸法表)

単位 長さ(mm) 質量 約(kg)

No.	A	B	C	D	E	F	G	使用 ボルト	適用 スイベルボルト	質量
TPU-200	19	38	100	63	14	14.5	M12	M 14	CHS-4000	0.53
TPU-202	19	38	150	88	14	14.5	M12	M 14	CHS-4000	0.87
TPU-204	25	50	100	62	14	17.0	M16	M 16	CHS-6000	0.68
TPU-206	25	50	150	87	14	17.0	M16	M 16	CHS-6000	1.05
TPU-207	25	50	175	103	14	17.0	M16	M 16	CHS-6000	1.58
TPU-208	30	50	150	88	20	20.5	M18	M 20	CHS-7000	1.34
TPU-209	30	50	175	103	20	20.5	M18	M 20	CHS-7000	1.90
TPU-210	30	50	200	125	20	20.5	M18	M 20	CHS-7000	1.40
TPU-211	38	65	200	123	24	25.0	M20	M 24	CHS-8000	3.30
TPU-212	38	65	250	148	24	25.0	M20	M 24	CHS-8000	4.10